

# ecomax™ 402

by **HOBART**



## Technical data

**Width / Depth / Height**  
435 / 530 / 700 mm

**Loading height**  
301 mm

**Rack size**  
385 x 385 mm  
396 x 396 mm

**Capacity per hour\***  
up to 40 racks

**Cycle times\***  
90 / 120 sec

**Wash / rinse temperature**  
approx. 60 °C /  
approx. 70 °C

**Tank capacity**  
11 l

**Fresh water consumption / cycle**  
2,5 l

**Wash pump**  
0,25 kW

**Booster loading**  
1,8 (3,7\*\*/5,5\*\*\*) kW

**Total loading**  
2,2 (4\*\*/5,9\*\*\*) kW

**Rated Voltage**  
230V / 50Hz / 1  
400V / 50Hz / 3

\* Hot water connection  
\*\* 20A  
\*\*\* 400/50/3N

## Glasswasher

## LOW PRICE – HIGH PERFORMANCE

### BEST RESULTS

- Rotating top and bottom wash system to distribute the wash water evenly over the glasses
- Thermostop-controlled rinse temperature

### EASY TO CLEAN

- Deep-drawn wash tank bottom, no hygiene problems with corners and edges
- Wash and rinse arms can be removed without tools

### ROBUST AND RELIABLE

- Double-walled door and solid suspension guarantee reliable operation in daily use
- Regular quality controls of all parts

### EASY TO USE

- Simple to handle
- Controls are easy to understand
- Loading height above average: 301mm, for easy loading of extra high glasses

### EASY TO SERVICE

- Easy access
- Drain pump and detergent dispenser can be retrofitted without any problems

- Double-walled insulated front door
- Automatic control of the rinse cycle
- Integrated rinse agent dispenser
- Heater with thermostatic control
- Incl. electrical cable and flexible water supply hose and drain hose
- Back panel
- Convertible from 230V/50Hz/1 to 400V/50Hz/3 at site

